

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

## \* 1 Identification

- **Product identifier**
- **Trade name:** ASP-16A DTM Primer
- **Article number:** ASP-16A
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Distributed by:  
OnPace Finishing Solutions  
15756 SE 130th Street  
Clackamas, OR 97015
- **Information department:** OnPace 866 569 9399
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## \* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 1)

· **Hazard pictograms**· **Signal word** Danger· **Hazard-determining components of labeling:**

acetone  
toluene  
butanone

· **Hazard statements**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P211 Do not spray on an open flame or other ignition source.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P264 Wash thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see on this label).  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P314 Get medical advice/attention if you feel unwell.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## \* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:**

Mixture: consisting of the following components.  
Weight percentages

- **Dangerous components:**

67-64-1 acetone	40 - 60%
68476-86-8 Petroleum gases, liquefied, sweetened	13 - 30%
108-88-3 toluene	7 - 10%
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5 - 5%
110-19-0 isobutyl acetate	1.5 - 5%
78-93-3 butanone	1.5 - 5%
763-69-9 ethyl 3-ethoxypropionate	1-1.5%
108-65-6 2-methoxy-1-methylethyl acetate	1-1.5%

## \* 4 First-aid measures

- **Description of first aid measures**

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## \* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

## \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**
- **PAC-1:**

67-64-1 acetone	200 ppm
108-88-3 toluene	67 ppm
110-19-0 isobutyl acetate	450 ppm
78-93-3 butanone	200 ppm
13463-67-7 titanium dioxide	30 mg/m <sup>3</sup>
763-69-9 ethyl 3-ethoxypropionate	1.6 ppm
108-65-6 2-methoxy-1-methylethyl acetate	50 ppm
2807-30-9 2-(propyloxy)ethanol	2.2 ppm
1330-20-7 xylene	130 ppm
1333-86-4 Carbon black	9 mg/m <sup>3</sup>
100-41-4 ethylbenzene	33 ppm
112926-00-8 precipitated Silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
67-56-1 methanol	530 ppm
95-63-6 1,2,4-trimethylbenzene	140 ppm
70657-70-4 2-methoxypropyl acetate	50 ppm
7727-43-7 barium sulphate, natural	15 mg/m <sup>3</sup>
57-55-6 Methyl glycol	30 mg/m <sup>3</sup>
78-83-1 butanol	150 ppm
21645-51-2 aluminium hydroxide	8.7 mg/m <sup>3</sup>

(Contd. on page 5)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

**Trade name: ASP-16A DTM Primer**

7631-86-9	<i>silicon dioxide, chemically prepared</i>	(Contd. of page 4) 18 mg/m3
<b>· PAC-2:</b>		
67-64-1	<i>acetone</i>	3200* ppm
108-88-3	<i>toluene</i>	560 ppm
110-19-0	<i>isobutyl acetate</i>	1300* ppm
78-93-3	<i>butanone</i>	2700* ppm
13463-67-7	<i>titanium dioxide</i>	330 mg/m3
763-69-9	<i>ethyl 3-ethoxypropionate</i>	18 ppm
108-65-6	<i>2-methoxy-1-methylethyl acetate</i>	1,000 ppm
2807-30-9	<i>2-(propyloxy)ethanol</i>	24 ppm
1330-20-7	<i>xylene</i>	920* ppm
1333-86-4	<i>Carbon black</i>	99 mg/m3
100-41-4	<i>ethylbenzene</i>	1100* ppm
112926-00-8	<i>precipitated Silica (Silica-Amorphous)</i>	200 mg/m3
67-56-1	<i>methanol</i>	2,100 ppm
95-63-6	<i>1,2,4-trimethylbenzene</i>	360 ppm
70657-70-4	<i>2-methoxypropyl acetate</i>	1,000 ppm
7727-43-7	<i>barium sulphate, natural</i>	170 mg/m3
57-55-6	<i>Methyl glycol</i>	1,300 mg/m3
78-83-1	<i>butanol</i>	1,300 ppm
21645-51-2	<i>aluminium hydroxide</i>	73 mg/m3
7631-86-9	<i>silicon dioxide, chemically prepared</i>	740 mg/m3
<b>· PAC-3:</b>		
67-64-1	<i>acetone</i>	5700* ppm
108-88-3	<i>toluene</i>	3700* ppm
110-19-0	<i>isobutyl acetate</i>	7500** ppm
78-93-3	<i>butanone</i>	4000* ppm
13463-67-7	<i>titanium dioxide</i>	2,000 mg/m3
763-69-9	<i>ethyl 3-ethoxypropionate</i>	110 ppm
108-65-6	<i>2-methoxy-1-methylethyl acetate</i>	5000* ppm
2807-30-9	<i>2-(propyloxy)ethanol</i>	140 ppm
1330-20-7	<i>xylene</i>	2500* ppm
1333-86-4	<i>Carbon black</i>	590 mg/m3
100-41-4	<i>ethylbenzene</i>	1800* ppm
112926-00-8	<i>precipitated Silica (Silica-Amorphous)</i>	1,200 mg/m3
67-56-1	<i>methanol</i>	7200* ppm
95-63-6	<i>1,2,4-trimethylbenzene</i>	480 ppm
70657-70-4	<i>2-methoxypropyl acetate</i>	5,000 ppm
7727-43-7	<i>barium sulphate, natural</i>	990 mg/m3
57-55-6	<i>Methyl glycol</i>	7,900 mg/m3
78-83-1	<i>butanol</i>	8000* ppm
21645-51-2	<i>aluminium hydroxide</i>	440 mg/m3

(Contd. on page 6)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

7631-86-9 silicon dioxide, chemically prepared

(Contd. of page 5)  
4,500 mg/m<sup>3</sup>

## \* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
 REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
 TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 594 mg/m<sup>3</sup>, 250 ppm  
 BEI

### 108-88-3 toluene

PEL Long-term value: 200 ppm  
 Ceiling limit value: 300; 500\* ppm  
 \*10-min peak per 8-hr shift  
 REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
 TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
 BEI

### 110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
 REL Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
 TLV Short-term value: 172 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

(Contd. on page 7)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

**Trade name: ASP-16A DTM Primer**

(Contd. of page 6)

**78-93-3 butanone**PEL Long-term value: 590 mg/m<sup>3</sup>, 200 ppmREL Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 590 mg/m<sup>3</sup>, 200 ppmTLV Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
BEI**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL Long-term value: 50 ppm

**· Ingredients with biological limit values:****67-64-1 acetone**

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

**108-88-3 toluene**

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L

Medium: urine

Time: end of shift

Parameter: Toluene

0.3 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

**78-93-3 butanone**

BEI 2 mg/L

Medium: urine

Time: end of shift

Parameter: MEK

**· Additional information:** The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 7)

- **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Safety glasses



Tightly sealed goggles

## \* 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:**

Aerosol

**Color:**

According to product specification

- **Odor:**

Characteristic

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

- **Change in condition**

**Melting point/Melting range:**

Undetermined.

**Boiling point/Boiling range:**

55 °C

- **Flash point:**

-103 °C

- **Flammability (solid, gaseous):**

Not applicable.

- **Ignition temperature:**

465 °C

- **Decomposition temperature:**

Not determined.

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 8)

- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
Avoid high heat
- **Explosion limits:**
  - Lower: 1.9 Vol %
  - Upper: 13.0 Vol %
- **Vapor pressure at 20 °C:** 233 hPa
- **Density at 20 °C:** 0.75323 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic: Not determined.
  - Kinematic: Not determined.
- **Solvent content:**
  - Organic solvents: 91.4 %
  - VOC content: 44.9 %
  - 587.2 g/l / 4.90 lb/gl
- **Solids content:** 8.5 %
- **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
  - Nitrogen oxides
  - Hydrocarbons
  - Carbon monoxide and carbon dioxide

## \*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
  - 108-88-3 toluene
  - Oral LD50 5000 mg/kg (rat)

(Contd. on page 10)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

**Trade name: ASP-16A DTM Primer**

(Contd. of page 9)

Dermal LD50 12124 mg/kg (rabbit)

Inhalative LC50/4 h 5320 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3 toluene	3
------------------	---

13463-67-7 titanium dioxide	2B
-----------------------------	----

1330-20-7 xylene	3
------------------	---

BENTONITE	suspected carcinogen <2% 14808-60-7
-----------	-------------------------------------

1333-86-4 Carbon black	2B
------------------------	----

100-41-4 ethylbenzene	2B
-----------------------	----

14807-96-6 Talc	3
-----------------	---

7631-86-9 silicon dioxide, chemically prepared	3
--	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5 montmorillonite clay complex

## \*12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 10)

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## \*14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **Transport hazard class(es)**
- **DOT**



- **Class** 2.1
- **Label** 2.1
- **ADR**



- **Class** 2 5F Gases
- **Label** 2.1
- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

(Contd. on page 12)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 11)

- **Packing group**
- **DOT, ADR, IMDG, IATA** Void
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Gases
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg
- **ADR**
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

## \*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**  
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
  - 108-88-3 toluene
  - Acrylic Resin
  - 78-93-3 butanone
  - 1330-20-7 xylene
  - 100-41-4 ethylbenzene

(Contd. on page 13)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

**Trade name: ASP-16A DTM Primer**

(Contd. of page 12)

67-56-1 *methanol*147-14-8 *Phthalocyanine Blue*95-63-6 *1,2,4-trimethylbenzene*7727-43-7 *barium sulphate, natural*14807-96-6 *Talc***· TSCA (Toxic Substances Control Act):**67-64-1 *acetone*108-88-3 *toluene*98-56-6 *4-chloro-alpha,alpha,alpha-trifluorotoluene*110-19-0 *isobutyl acetate*78-93-3 *butanone*13463-67-7 *titanium dioxide*763-69-9 *ethyl 3-ethoxypropionate*108-65-6 *2-methoxy-1-methylethyl acetate*16883-83-3 *benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate*2807-30-9 *2-(propyloxy)ethanol*1330-20-7 *xylene*51274-00-1 **YELLOW IRON OXIDE**1333-86-4 *Carbon black*64742-82-1 *Naphtha (petroleum), hydrodesulfurized heavy*68911-87-5 *montmorilontie clay complex*100-41-4 *ethylbenzene*1332-37-2 *Iron oxide*61791-55-7 *Amines, N-tallow alkyltrimethylenedi-*64742-95-6 *Solvent naphtha (petroleum), light arom.*67-56-1 *methanol*147-14-8 *Phthalocyanine Blue*95-63-6 *1,2,4-trimethylbenzene*7727-43-7 *barium sulphate, natural*14807-96-6 *Talc*57-55-6 *Methyl glycol*78-83-1 *butanol*21645-51-2 *aluminium hydroxide*7631-86-9 *silicon dioxide, chemically prepared*7732-18-5 *water***· Proposition 65****· Chemicals known to cause cancer:**13463-67-7 *titanium dioxide*1330-20-7 *xylene*1333-86-4 *Carbon black*100-41-4 *ethylbenzene*95-63-6 *1,2,4-trimethylbenzene*

(Contd. on page 14)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

**Trade name: ASP-16A DTM Primer**

(Contd. of page 13)

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

67-56-1 methanol

- **Carcinogenity categories**

- **EPA (Environmental Protection Agency)**

67-64-1 acetone

I

108-88-3 toluene

II

78-93-3 butanone

I

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

95-63-6 1,2,4-trimethylbenzene

II

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

- **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

108-88-3 toluene

A4

13463-67-7 titanium dioxide

A4

1330-20-7 xylene

A4

1333-86-4 Carbon black

A4

100-41-4 ethylbenzene

A3

14807-96-6 Talc

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

67-56-1 methanol

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS04



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

toluene

butanone

(Contd. on page 15)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

Trade name: ASP-16A DTM Primer

(Contd. of page 14)

- **Hazard statements**

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P211 Do not spray on an open flame or other ignition source.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321 Specific treatment (see on this label).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## \*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Regulatory Affairs Department

- **Contact:** 866 569 9399

- **Date of preparation / last revision** 01/05/2017 / 15

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 16)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/05/2017

Reviewed on 01/05/2017

**Trade name: ASP-16A DTM Primer**

(Contd. of page 15)

EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flam. Aerosol 1: Aerosols – Category 1  
Press. Gas: Gases under pressure – Compressed gas  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
\* **Data compared to the previous version altered.**

USA